

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 25638

1. OWNER Monte Gillespie ADDRESS AT WELL LOCATION 4600 N. Virginia Street  
MAILING ADDRESS 120 2nd Street Street  
Reno, NV 89501 Reno, NV 89501

2. LOCATION SW 1/4 NW 1/4 Sec. 26 T. 20 N. S. R. 19 E Washoe County  
PERMIT NO. M/O 717 C&B N/A N/A  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

| Material   | Water Strata | From | To  | Thick-ness |
|--|--------------|------|-----|------------|
| GM MW -9   |              |      |     |            |
| Tan green white rock w/streaks of clay                           |              | 0    | 47  | 47         |
| Brown clay with streaks of green white rock                      |              | 47   | 85  | 38         |
| Purple green rock (coarse)                                       | 85           | 85   | 110 | 25         |
| Premie in #8 -12 silica sand -110' to -14'                       |              |      |     |            |
| 3/8 chip bentonite seal placed from -12' to -14'                 |              |      |     |            |
| Well monument cemented in flush with surface with concrete grout |              |      |     |            |

8. WELL CONSTRUCTION  
Depth Drilled 110 Feet Depth Cased 110 Feet

HOLE DIAMETER (BIT SIZE)  
From To  
10 Inches 0 Feet -110' Feet  
Inches Feet Feet  
Inches Feet Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 4"                 | PVC                 | Sch 40                  | -3"         | 110       |

Perforations:  
Type perforation slots  
Size perforation .020  
From -15 feet to -110 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal 12  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
From -14' feet to -110' feet

9. WATER LEVEL  
Static water level 53 feet below land surface  
Artesian flow N/A G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started June 7, 1994  
Date completed June 8, 1994

7. WELL TEST DATA

| TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift |                               |              |  |
|--|-------------------------------|--------------|--|
| G.P.M.   | Draw Down (Feet Below Static) | Time (Hours) |  |
|  | <u>N/A</u>                    |              |  |

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Hackworth Drilling, INC. Contractor  
Address P.O. Box 850 Contractor  
Elko, NV 89803

Nevada contractor's license number issued by the State Contractor's Board 020582  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1654

Signed John C. Smith  
By driller performing actual drilling on site or contractor  
Date July 6, 1994