WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45884
Permit No.
Basin

NOTICE OF INTENT NO. 26795

1. OWNER Philip & Debbie Snyder
MAILING ADDRESS 1677 Hyde St. Gardnerville NV 89401
ADDRESS AT WELL LOCATION 1677 Hyde St. Gardnerville NV 89401

2. LOCATION NE ¼ SW ¼ Sec. 2 T. 13 N/S R. 20 E. Douglas County
PERMIT NO. (Issued by Water Resources) 23-530-01 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☑ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Cobbles and Small Sands		0	45	45
3/4" Gravels w/small Dry Clay Balls		45	60	15
Brown Dry Clay		60	75	15
Inbeded Gravels		75	84	9
Brown Clay		84	95	11
Course Obsidian Sands		95	115	20
Brown Clay Zone		115	178	63
Inbeded Sands and Course Gravels w/clay Seams		178	210	32
Course DG Sands	XXX	210	260	50
TD 260'				
GPM 20				

Date started 8-30, 1994
Date completed 9-2, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20	35	3 HRS

8. WELL CONSTRUCTION
Depth Drilled 260 Feet Depth Cased 260 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11 1/4	Inches	0 Feet	260 Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	0	260

Perforations:
Type perforation Mill Slot
Size perforation 3 x 3/32
From 220 feet to 260 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 105
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 105 feet to 260 feet

9. WATER LEVEL
Static water level 180 feet below land surface
Artesian flow G.P.M. 20 P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H Pump Co. (Contractor)
Address 5551 Hwy 50 E #3 (Contractor)
Carson City NV 89701
Nevada contractor's license number issued by the State Contractor's Board 31839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1472
Signed Quinton K. Butts (By driller performing actual drilling on site or contractor)
Date 9-3-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627