WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45889
Permit No.
Basin 105

NOTICE OF INTENT NO. 26572

1. OWNER BOB MURRAY CONST.
MAILING ADDRESS GARDNERVILLE, NV
ADDRESS AT WELL LOCATION 721 CUTTER GARDNERVILLE

2. LOCATION NE ¼ NE ¼ Sec. 25 T. 12 N/S R. 20 E. DOUGLAS County
PERMIT NO. — (Issued by Water Resources) 29-432-27 (Parcel No.) RUHENSTROTH (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other MVD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SANDY CLAY		0	11	11
CEMENTED GRAVEL		11	14	3
SANDY CLAY		14	46	32
CEMENTED GRAVEL		46	53	7
SANDY CLAY		53	68	15
CLAY		68	106	38
SANDY CLAY W/GRAVEL		106	115	9
CEMENTED GRAVEL		115	124	9
SANDY CLAY W/GRAVEL		124	132	8
CEMENTED GRAVEL	✓	132	160	28

'94 SEP -8 A10:45
STATE ENGINEER'S OFFICE

Date started 8-11, 1994
Date completed 8-17, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AIR	20+	—	1

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	160 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13	.188	0	160

Perforations:
Type perforation FACTORY SLOTTED
Size perforation 3 x 3/32
From 140 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 160 feet

9. WATER LEVEL
Static water level 83 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature COLD °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EDDCO EXPLORATION (Contractor)
Address 7780 CURRY RD (Contractor)
FALLON, NV 89406
Nevada contractor's license number issued by the State Contractor's Board 27673
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1726
Signed Patrick A. Moore (By driller performing actual drilling on site of contractor)
Date 8-17-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627