

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT  
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 26907

1. OWNER Ray Swanson ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 10368 Fareway Antelope Valley Battle Mtn.  
Hanford, CA 93230  
 2. LOCATION SE 1/4 SW 1/4 Sec. 31 T. 25 N S. R. 41 E. Lander County  
 PERMIT NO. 49558 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	4	4
Sand & gravel		4	22	18
Brown clay w/some sand		22	28	6
Sand & gravel		28	44	16
Brown clay		44	55	11
Sand & gravel		55	60	5
Brown clay		60	64	4
Sand & gravel		64	71	7
Sand & brown clay		71	104	33
Sand & gravel w/brown clay		104	108	4
Pea gravel		108	117	9
Sand & clay		117	140	23
Sand		140	144	4
Sand & gravel w/clay		144	146	2
Sand & clay		146	152	6
Pea gravel		152	161	9
Brown clay		161	195	34
Sand & gravel w/some clay		195	210	15
Brown clay w/some sand		210	218	8
Sand & gravel		218	220	2
Sand & gravel w/some clay		220	223	3
Sand & gravel		223	228	5
Clay w/some sand		228	248	20
Sand & gravel w/some clay		248	250	2
Sand & gravel		250	258	8
Sand		258	270	12
Brown clay w/some sand		270	276	6
Sand & gravel w/some clay		276	280	4
Sand/gravel/clay		280	295	15

8. WELL CONSTRUCTION  
 Depth Drilled 350 Feet Depth Cased 310 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 30 Inches To 0 Feet 350 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42	1/4	+2	100

Perforations:  
 Type perforation Please see page 2 for  
 Size perforation this information.  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Depth of Seal 50' 24" conductor  Cement Grout  
 Placement Method:  Pumped  Concrete Grout  
 Poured  
 Gravel Packed:  Yes  No  
 From 0 feet to 350 feet

9. WATER LEVEL  
 Static water level 88 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Humboldt Drilling & Pump Co., Inc. Contractor  
 Address P.O. Box 590 Contractor  
Winnemucca, NV 89446  
 Nevada contractor's license number issued by the State Contractor's Board 015234  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154  
 Signed Mary D. Sompkins ma  
 By driller performing actual drilling on site or contractor  
 Date 9/14/94

Date started June 27, 1994  
 Date completed June 29, 1994

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
<u>2400</u>	<u>180'</u>	<u>8</u>	
	<u>actual</u>		
	<u>pumping level</u>		
	<u>STATIC</u>		

