WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45926
Permit No.
Basin 059

NOTICE OF INTENT NO. 26868

1. OWNER Battle Mountain Gold
MAILING ADDRESS P.O. Box 1627
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION
Copper Canyon Battle Mountain

2. LOCATION SW ¼ SE ¼ Sec. 27 T. 31 N/S R. 43 E Lander County
PERMIT NO. M/O 651-B C01-32 (Issued by Water Resources) NA (Parcel No.) NA (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Granite		0	68	68
Shale		68	140	72
Granite		140	155	15
Quartzite		155	255	100
Shale		255	275	20
Quartzite		275	460	185

Date started June 1, 1994
Date completed June 5, 1994

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1.213.2		air on rig

8. WELL CONSTRUCTION
Depth Drilled 460 Feet Depth Cased 460 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/4 Inches		0 Feet	460 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	0	260
1	PVC	SCH 80	0	260

Perforations:
Type perforation Screen
Size perforation 50 slot 1/8 X 1/4
From 2" 260 feet to 460 feet
From 1" 260 feet to 460 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No Silica Sand #10 X 20
From 50 feet to 460 feet

9. WATER LEVEL
Static water level 215.32 feet ~~below land surface~~ from top of casing
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed C. E. Eppler (By driller performing actual drilling on site or contractor)
Date 7-19-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627