WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45927 45928
Permit No.
Basin 059

NOTICE OF INTENT NO. 26865

1. OWNER Battle Mountain Gold
MAILING ADDRESS P.O. Box 1627
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION
Copper Basin Battle Mountain

2. LOCATION SW ¼ SW ¼ Sec. 28 T. 32 N/S R. 44 E. Lander County
PERMIT NO. M/O-651-B CON-1 (Issued by Water Resources) NA (Parcel No.) NA (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Cherty argillito		0	50	50
Quartzite		50	65	15
Altered intimsive		65	105	40
Brown chert		105	125	20
Siltstone		125	190	65
Chert gray/white		190	407	217

'94 JUL 22 A11:20
STATE ENGINEER'S OFFICE

Date started June 18, 19 94
Date completed June 22, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
		air on rig

8. WELL CONSTRUCTION
Depth Drilled 407 Feet Depth Cased 407 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
6 3/4	0	405

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	0	265
1	PVC	SCH 80	0	285

Perforations:
Type perforation Screen
Size perforation 50 slot 1/8 X 1/4
From 2" 265 feet to 400 feet
From 1" 285 feet to 400 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No Silica sand#10 X 20
From 50 feet to 405 feet

9. WATER LEVEL
Static water level 176.05 feet ~~below land surface~~ from top of casing
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed C. C. Eggler (By driller performing actual drilling on site or contractor)
Date 7-19-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627