WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45930
Permit No.
Basin 059

NOTICE OF INTENT NO. 26866

1. OWNER Battle Mountain Gold
MAILING ADDRESS P.O. Box 1627
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION
Copper Basin Battle Mountain

2. LOCATION NE ¼ NE ¼ Sec. 32 T 32 N/S R 44 E Lander County
PERMIT NO. M/O 651-B CON-2 (Issued by Water Resources) | NA (Parcel No.) | NA (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Quartz monznite pophry		0	270	270
Quartz monznite pophry mixed w/chert and siltstone		270	330	60
Quartz monznite pophry		330	407	77

'94 JUL 22 AM 10:20 STATE ENGINEER'S OFFICE

Date started June 22, 19 94
Date completed June 23, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 407 Feet Depth Cased 405 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/4 Inches		0 Feet	407 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	0	265
1	PVC	SCH 80	0	285

Perforations:
Type perforation Screen
Size perforation SCH 80
From 2" 265 feet to 405 feet
From 1" 285 feet to 405 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No Silica Sand #10 X 20
From feet to feet

9. WATER LEVEL
Static water level 389.1 feet ~~below land surface~~ from top of casing
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed C. E. Eyler (By driller performing actual drilling on site or contractor)
Date 7-19-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627