WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46315
Permit No.
Basin 064

NOTICE OF INTENT NO. 26915

1. OWNER 26 Ranch
MAILING ADDRESS P. O. Box 3094
Elko, NV 89803

ADDRESS AT WELL LOCATION 20 miles north of Battle Mountain

2. LOCATION NE ¼ SE ¼ Sec. 9 T. 35 N/S R. 45 E. Lander County

PERMIT NO. (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
sand		0	10	10
sandy clay		10	35	25
volcanic sand		35	40	5
clay		40	43	3
sand & gravel		43	50	7
clay		50	58	8
hard volcanic		58	68	10
volcanic sand		68	160	92
clay		160	203	43
volcanic sand		203	216	13
sandy clay		216	230	14
volcanic w/fractures		230	270	40

Date started August 20, 19 94
Date completed August 21, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		1 hr.

8. WELL CONSTRUCTION
Depth Drilled 270 Feet Depth Cased 270 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	270 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+2	220
6 5/8	12.92	.188	260	270

Perforations:
Type perforation mill slot
Size perforation 1/8 x 3
From 220 feet to 260 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 100
Placement Method: ☒ Pumped ☐ Poured

Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 100 feet to 270 feet

9. WATER LEVEL
Static water level 20 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature norm °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co. Inc. (Contractor)
Address P. O. Box 590 (Contractor)
Winnemucca, NV 89446

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed C. E. Eggle
(By driller performing actual drilling on site or contractor)
Date 9-24-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627