WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46376
Permit No.
Basin 092B

NOTICE OF INTENT NO. 22874

1. OWNER STEVE WANDT
MAILING ADDRESS 11895 Fir Drive
Reno, NV 89506

ADDRESS AT WELL LOCATION
Same

2. LOCATION SE ¼ NW ¼ Sec. 15 T 21N N/S R 19 E Washoe County
PERMIT NO. (Issued by Water Resources) 080-385-02 (Parcel No.) Lemmon VAlely (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☒ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Static water level @ 225 feet				
Total depth @230 feet.				
WELL DEEPNING:				
Rust, small rock & sand		230	233	3
Hard bottom. Broken & fractured granite	X	233	242	9
Granite		242	248	6
Broken & fractured granite		248	253	5
Granite		253	264	11
Weathered granite, softer		264	269	5
Very soft zone		269	275	6
Weathered granite, medium hard		275	283	8
Weathered grnaite, softer zone	X?	283	288	5
Fractured granite		288	294	6
Granite		294	311	17
Open fracture	X	311	313	2
Granite		313	328	15
Broken fractured & weathered granite	X	328	338	10

Date started 9-12-94, 19
Date completed 9-13-94, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10		

8. WELL CONSTRUCTION
Depth Drilled 338 Feet Depth Cased 340 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6" Inches	230 Feet	338 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5"OD		.188	0	340

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 218 feet to 258 feet
From 278 feet to 298 feet
From 318 feet to 338 feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal deepening
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 230 feet to 338 feet

9. WATER LEVEL
Static water level 218 feet below land surface
Artesian flow G.P.M. 10 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed (By driller performing actual drilling on site or contractor)
Date September 16, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627