WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46392
Permit No.
Basin 084

NOTICE OF INTENT NO. 17741

1. OWNER Rockwell International Rocketdyne Div.
MAILING ADDRESS 6633 Canoga Ave. Canoga Park, CA91303
ADDRESS AT WELL LOCATION former Rockwell Nevada field Lab in Palamino Valley Nevada 2.4 miles Whiskey Spr Rd.

2. LOCATION SE ¼ NE ¼ Sec. 07 T 22N N/S R 22E E Washoe County
PERMIT NO. Waiver M/O-431-B (Issued by Water Resources) 77-320-0[illegible] (Parcel No.) n/a Palomino Valley Unit VI 2 2 3 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [ ] Other HSA

#1 6. Vapor Extraction LITHOLOGIC LOG Area D

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Gravelly Sany | | 0 | 18 | fine |
| Gravelly Sand | | 18 | 35 | fine |
| Clayey Sand | | 35 | 38 | med |
| Clayey Silt/Silty clay | | 38 | 42 | moist |

Date started 5/27, 1994
Date completed 5/27, 1994

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| n/a | | | |

8. WELL CONSTRUCTION
Depth Drilled 42.0 Feet Depth Cased 42.0 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 8.75 Inches | 0 Feet | 42.0 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 2-3/8 | sch40 | n/a | 1.6 | 38.9 |

Perforations:
Type perforation factory sawed
Size perforation .020
From 28.4 feet to 38 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 24'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
Gravel Packed: [X] Yes [ ] No with 2' bentonite barrier
From 26 feet to 42 feet

9. WATER LEVEL
Static water level n/a feet below land surface
Artesian flow n/a G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hedman Drilling Co. (Contractor)
Address P.O. Box 726 (Contractor)
Lincoln, CA 95648
Nevada contractor's license number issued by the State Contractor's Board 0033492
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1555
Signed Steve Hedman (By driller performing actual drilling on site or contractor)
Date 5/27/94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627