

OFFICE USE ONLY  
 Log No. 46399  
 Permit No. 084  
 Basin 084

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**  
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 17741

1. OWNER Rockwell International-Rocketdyne ADDRESS AT WELL LOCATION former Rockwell  
 MAILING ADDRESS Div 6633 Conaga Ave. Nevada field lab in Palamino Valley  
Conaga Park, CA 91303 Nevada 2240 Whiskey Springs Rd  
 2. LOCATION SE 1/4 NE 1/4 Sec. 07 T. 22N N/S R. 22E E Washoe County  
 PERMIT NO. Waiver M/O-431-B 77-320-079 n/a Palamino J. Unit 11 T. 22 S  
Issued by Water Resources Parcel No. Subdivision Name

3. PS-3/V-3 WORK PERFORMED Area D  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other.....  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Gravelly Sand		0	7	med
Gravelly Sand		7	25	f-course
Gravelly Sand		25	35	m-course
Clayey Sand		35	41	gravel
Silty Clay/Clayey silt		41	50	v. fine
Gravelly Sand		50	55.5	med

94 SEP -6 P 3:53  
 STATE ENGINEERS OFFICE  
 Dual Comp  
 See Log # 46400

8. WELL CONSTRUCTION  
 Depth Drilled 55.5 Feet Depth Cased 55.5 Feet

HOLE DIAMETER (BIT SIZE)  
 From 0 Feet To 55.5 Feet  
8.75 Inches 0 Feet 55.5 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2-3/8	sch40	n/a	0	55.5 PS-3
1-5/16	sch80	n/a	2.3	43. V-3

Perforations: factory sawed  
 Type perforation \_\_\_\_\_  
 Size perforation .020  
 From 38.4 feet to 42.7 feet V-3  
 From 50.4 feet to 54.6 feet PS-3  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 34'  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
with V-3 2" and PS-3 5" bentonite  Concrete Grout  
barrier  
 Gravel Packed:  Yes  No  
 From V-3 36' feet to 43' feet  
 From PS-3 48' feet to 55.5' feet

9. WATER LEVEL  
 Static water level 48.2 feet below land surface  
 Artesian flow n/a G.P.M. n/a P.S.I.  
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Hedman Drilling Co. Contractor  
 Address P.O. Box 726 Contractor  
Lincoln, CA 95648  
 Nevada contractor's license number issued by the State Contractor's Board 0033492  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1555  
 Signed Steve Hedman  
 By driller performing actual drilling on site or contractor  
 Date 6/8/94

Date started 6/8 1994  
 Date completed 6/8 1994

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
n/a			