Permits 68067-90

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

25 ACAB

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46508
Permit No. 65726
Basin 084

NOTICE OF INTENT NO. 26294

1. OWNER George & Elaine Capurro
MAILING ADDRESS 4055 Bacon Rind
Reno Nevada 89
ADDRESS AT WELL LOCATION Same
N39.749432 W119.683583 NAD27

2. LOCATION SW ¼ NE ¼ Sec. 25 T. 22 N/S R. 20 E. Washoe County
PERMIT NO. 30110 (Issued by Water Resources) 076-162-05 (Parcel No.) Palomino V. Unit 5 25-2-03 (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☑ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay, Sandy		0	10	10
Sand		10	16	6
Clay, brown		16	23	7
Gravel, to ½"		23	31	8
Clay, Sand		31	64	33
Clay, Compacted, tan		64	106	42
Gravel to 3/8"		106	118	12
Clay, Grey, hard		118	193	75
Clay, brown		193	235	42
Gravel, 3/8" Plus		235	241	6
Clay, Grey		241	304	63
Volcanics		304	352	48
Rock, tan, Fine Grained		352	375	23
Clay, Grey, Soft		375	453	78
Clay, Green, Soft		453	468	15
Rock, white, Pink, Grey		468	560	92
W/ Clay Streaks				

Date started 6-21, 1994
Date completed 7-5, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
400	—	4

8. WELL CONSTRUCTION
Depth Drilled 560 Feet Depth Cased 560 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12¼ Inches		0 Feet	560 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8⅝	16.94	0.188	0	560

Perforations:
Type perforation Factory Mill Slot
Size perforation 3/32
From 100 440 feet to Staggered feet
From 440 feet to 560 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 55 feet to 560 feet

9. WATER LEVEL
Static water level 74 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name McKay Drilling (Contractor)
Address 2290 Pioneer Drive (Contractor)
Reno, Nevada 89509
Nevada contractor's license number issued by the State Contractor's Board 14170
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1652
Signed Steve McKay (By driller performing actual drilling on site or contractor)
Date 8/8/94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627