VD 94-3

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46539
Permit No.
Basin 061

NOTICE OF INTENT NO. 25612

1. OWNER BARRICK GOLDSTRIKE MINE
MAILING ADDRESS P.O. BOX 29
ELKO NEVADA 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION SW ¼ NW ¼ Sec. 30 T. 36 N/S R. 50 E. EUREKA County
PERMIT NO. M/0-441 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [X] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DRONITE OXIDIZED		0	40	40
DRONITE GREY GREEN		40	200	160
DRONITE & CLAYSS	TRACE	200	320	120
FRACTURED DRONITE GRAY TO DARK GREY HARD	TRACE	320	460	140
DRONITE GREY TO DARK GREY	1	460	580	120
FRACTURED GREY GREEN DORNITE	2	580	600	20
HARD GREY GREEN DORNITE	2	600	660	60
HARD GREY DORNITE	6	660	840	180
HARD GRANULATED ROCK SMALL FRACTURES	7	840	1000	160

Date started JUNE 25, 1994
Date completed JUNE 27, 1994

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1000 Feet Depth Cased 1000 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12-1/4 Inches		0 Feet	21 Feet
6-3/4 Inches		21 Feet	1000 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	24.7	.322	0	21
2	2.25	SCH 80	0	200

Perforations:
Type perforation SLOT
Size perforation 1/8" X 2"
From 200 feet to 1000 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 52
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level NONE feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UT 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1822
Signed Ron Thompson (By driller performing actual drilling on site or contractor)
Date July 5, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627