WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 46632
Permit No.
Basin 087

NOTICE OF INTENT NO. 26483

1. OWNER GEORGE & GLEE FRYER
MAILING ADDRESS 7530 Wimbelton
Reno, NV 89511

ADDRESS AT WELL LOCATION 70 Cassas Crt.
Reno, NV 89511

2. LOCATION SW ¼ SE ¼ Sec. 2 T. 18N N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 041-120-41 (Parcel No.) SW Reno (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Reddish brown soft volcanic rock		1	9	8
Brown volcanic rock		9	63	54
Rusty brown volcanic rock		63	86	23
Yellow volcnic rock		86	106	20
Fracture rock (app 3GPM)	X	106	111	5
Yellow volcanic rock		111	115	4
Fracture (NO WATER)		115	116	1
Yellow volcanic rock		116	118	2
Brown volcanic rock		118	127	9
Fracture (NO WATER)		127	128	1
Brown volcanic rock		128	138	10
Yellow volcanic rock		138	172	34
Fracture	X	172	187	15
Yellow volcanic rock		187	200	13

'94 NOV 18 A11:11 STATE ENGINEER

Date started 11-8-94, 19
Date completed 11-9-94, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	100	Feet
8 5/8	Inches	100	Feet	200	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	200

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 155 feet to 195 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout
Gravel Packed: [X] Yes [ ] No
From 100 feet to 200 feet

9. WATER LEVEL
Static water level 77 feet below land surface
Artesian flow G.P.M. 30 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date November 12, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627