

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO20718

Consultant: \_\_\_\_\_  
 1. OWNER: Steffen Roberson and Kirsten  
 MAILING ADDRESS: 1755 E. Plumb Lane Suite 241  
Reno, NV 89502  
 ADDRESS AT WELL LOCATION: Winners Corner  
1600 B ST./ 1600 Victoria Ave.  
Sparks, NV  
 2. LOCATION: SE  $\frac{1}{4}$  SW  $\frac{1}{4}$  Sec. 5 T. 19N N/S R. 20 E. Washoe County  
 PERMIT NO. M/O#655-C MW#7 032-122-18  
 Issued by Water Resources Parcel No. Subdivision Name Sparks

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Tubex \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt		0	3	3
Aggregate Base		3	2.5	.5
Brown Silty Sand: with trace gravel; non-plastic, loose, slightly moist.		2.5	12.5	10
Dark Brown Silty Gravel with some cobbles, non-plastic, loose saturated		12.5	18	6.5
Light Brown Silty Gravel non-plastic, loose, saturated		18	34	16

8. WELL CONSTRUCTION  
 Depth Drilled 34 Feet Depth Cased 18.5 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
9 5/6 Inches 0 Feet 34 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	18.5
4" PVC Spargeline		SCH 40	0	34
2" PVC Sparge head		SCH 40		

Perforations:  
 Type perforation Factory Sawned Slot  
 Size perforation 0.20  
 From 8.5 feet to 18.5 feet 4"  
 From 32 feet to 34 feet 2"  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 0-6  Neat Cement  
 Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite Seal: 6 to 7 feet and 25-29'  
 Gravel Packed:  Yes  No #8 Silica Sand  
 From 7-25 feet to 29-34 feet

9. WATER LEVEL  
 Static water level 17.8 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. N/A P.S.I.  
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling Inc. Contractor  
 Address P.O. Box 12370 Contractor  
Reno, NV 89510  
 Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed Wayne Drilling Inc.  
 By driller performing actual drilling on site or contractor  
 Date February 28, 1995

7. WELL TEST DATA  
 TEST METHOD:  Bailer  Pump  Air Lift  

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No Test			

 Date started 5/11/94 19\_\_\_\_\_  
 Date completed 5/11/94 19\_\_\_\_\_