

Log No. **46994**
 Permit No. _____
 Basin. **087**

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 22859

Consultant:

1. OWNER Kennedy/ Jenks Consultant ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS 5190 Neil Road, Suite 300 Nevada Meat Packing, Inc.
Reno, Nevada 89502 475 Nugget Avenue Sparks, Nevada
 2. LOCATION NW 1/4 NW 1/4 Sec. 9 T 19N N/S R. 20 E Washoe County
 PERMIT NO. M/O 886-NM#1 032-220-65 Sparks
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED 4. PROPOSED USE 5. WELL TYPE
 New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC
 Deepen Abandon Other _____ Municipal/Industrial Monitor Stock Air Other Tubex _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphaltic Concrete Pavement:		0	1/2	
Silty Sand with Gravel Moist, derd brown; sane is fine- to mediun-grained; gravel to 1' (15%); occasional cobbles to 6 inches, rounded; bite of railroad timber noted at 2ft Cuttings from approx 5.5 to 7 feet are dark brown to black, wet.		1/2	9	
Poorly-graded Gravel with Sand: Moist, yellow brown; gravel sub-angular to rounded to 1':sand is medium-to coarse grained (30%-40%); 5% fines; occasional cobbles to 6" Large cobbles (to 36" dia.) present from 13 to 15 feet as noted by driller.		9	14 1/2	

Continued on Page 2

8. WELL CONSTRUCTION
 Depth Drilled 38.3 Feet Depth Cased 38.3 Feet
 HOLE DIAMETER (BIT SIZE)
 From _____ To _____
9.5/16 Inches _____ Feet 38.3 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4' PVC		sch 40	0	38.3

 Perforations:
 Type perforation Factory sawed slot
 Size perforation 0.02
 From 18.3 feet to 38.3 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 0-14.3 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal; 14.3-16.3 Colorado Silica Sand
 Gravel Packed: Yes No
 From 16.3 feet to 38.3 feet

Date started 12/20/94, 19_____
 Date completed 12/21/94, 19_____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No Test			

9. WATER LEVEL
 Static water level 25.4 feet below land surface
 Artesian flow _____ G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date December 30, 1994

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No.
 Permit No.
 Basin.....

Page 2 Of 2 pages
 NOTICE OF INTENT NO. 22549

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK
 Consultant:

1. ~~OWNER~~ Kennedy/Jenks Consultant ADDRESS AT WELL LOCATION
 MAILING ADDRESS 5190 Neil Road, Suite 300 Nevada Meat Packing, Inc.
 Reno, Nevada 89502 475 Nugget Avenue
 2. LOCATION NW 1/4 NW 1/4 Sec 9 T 19N N/S R 20 E Washoe County
 PERMIT NO. M/O 886-NW#1 032-220-65
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED 4. PROPOSED USE 5. WELL TYPE
 New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC
 Deepen Abandon Other Municipal/Industrial Monitor Stock Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Continued from page 1				
Well-graded Sand with Silt and Gravel. Moist, dark yellow brown; sand is fine to medium-grained; gravel (25%); silt (10%); cobbles up to 8 in. dia.		14 1/2	22	
Silty Sand with Gravel. Moist to wet, brown to red brown; sand is medium to coarse grained; gravel (30-40%) to 1", rounded to sebrounded; silt (15%); large cobbles noted by driller at 24 feet; little clay.		22	33	
Silty Sand: Wet, yellow brown; sand is fine to medium grained; silt (20-30%); clay (10%); gravel (10%) to 1" dia.		33	38.3	

8. WELL CONSTRUCTION
 Depth Drilled.....Feet Depth Cased.....Feet
 HOLE DIAMETER (BIT SIZE)
 From To
Inches.....Feet.....Feet
Inches.....Feet.....Feet
Inches.....Feet.....Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
 Type perforation.....
 Size perforation.....
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout
 Depth of Seal.....
 Placement Method: Pumped Poured
 Gravel Packed: Yes No
 From.....feet to.....feet

9. WATER LEVEL
 Static water level.....feet below land surface
 Artesian flow.....G.P.M.....P.S.I.
 Water temperature.....°F Quality.....

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc. Contractor
 Address P.O. Box 12370 Contractor
 Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed December 30, 1994
 By driller performing actual drilling on site or contractor
 Date

Date started 12/20/94, 19.....
 Date completed 12/20/94, 19.....

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No Test			