

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 22869

1. OWNER Larry Paul ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS 60 Shady View 2450 View Point
Sparks, NV 89436 Spanish Springs
 2. LOCATION SE 1/4 NE 1/4 Sec 8 T. 21N N/S R. 21 E Washoe County
 PERMIT NO. 076-300-35 Spanish Springs
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Fill Brown clay & Boulders in ditch		0	3.5	3.5
Green Broken Volcanic Rock		3.5	34	30.5
Brown Volcanic		34	96	62
Light Brown Volcanic		96	118	22
White Clay		118	136	18
Light Brown Clay		136	167	31
Red Volcanic Rock		167	247	80
Brown Broken Volcanic Rock	x	247	253	6
Soft Brown Volcanic Rock		253	280	27
Brown Volcanic Rock		280	291	11
Clay Streak		291	294	3
Brown Volcanic Rock		294	315	21
Gray Granite		315	343	28
Fracture (No Water)		343	344	1
Gray Granite		344	378	30
Soft Zone (No Water)		378	381	3
Gray Granite		381	395	14

8. WELL CONSTRUCTION
 Depth Drilled 395 Feet Depth Cased 395 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
10 Inches 0 Feet 50 Feet
8 5/8 Inches 50 Feet 395 Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	395

 Perforations:
 Type perforation Factory Sawn slot
 Size perforation 3/32 x 3 x 5 around
 From 390 feet to 370 feet
 From 330 feet to 310 feet
 From 270 feet to 250 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 50 _____ Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 395 feet

Date started 2/27/95, 19_____
 Date completed 3/1/95, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
8		

9. WATER LEVEL
 Static water level: 212 feet below land surface
 Artesian flow _____ G.P.M. 8 P.S.I.
 Water temperature cold °F Quality clear
 10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources the on-site driller 923
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date March 7, 1995