WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49278
Permit No.
Basin 091

NOTICE OF INTENT NO. 27303

Consultant:

1. ~~OWNER~~ SUMMIT ENGINEERING CORPORATION
MAILING ADDRESS 5405 Mae Ann Avenue
Reno, Nevada 89523

Client:
ADDRESS AT WELL LOCATION
Boomtown Hotel & Casino, Inc. P.O. Box 399
Verdi, Nevada 89439

2. LOCATION NW ¼ NW ¼ Sec. 16 T. 19N N/S R. 18E E. Washoe County
PERMIT NO. M/O #852 MW#1 (Issued by Water Resources) Parcel No.
Pony Express Station, Boomtown (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill, Silty sands & gravel, moist brown		0	24½	24½
Sandy gravel, abundant cobbles & boulders granitic composition of lithics, moist, greenish-gray		24½	40	15½
Clean sand, occasional gravel, moist, brown		40	45½	5½
Sandy gravle, abundant cobbles & boulders granitic composition of lithics, moist, greyish-brown		45½	89	43½

'94 NOV 21 P1:41
STATE ENGINEER

Date started 9-26-94, 19
Date completed 9-28-94, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

8. WELL CONSTRUCTION
Depth Drilled 89 Feet Depth Cased 89 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 5/16 Inches	0 Feet	89 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		sch 40	0	89
PVC bottom plug				

Waterproof Lockin cap/Christy box/ground surface

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1½ x 6 rows
From 54 feet to 89 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 5 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite seal: 5 feet to 52 feet
Gravel Packed: ☒ Yes ☐ No Monteray Sand
From 52 feet to 89 feet

9. WATER LEVEL
Static water level 64.75 feet below land surface
Artesian flow G.P.M. not known P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date November 17, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627