WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 47487
Permit No.
Basin 093A

NOTICE OF INTENT NO. 27308

1. OWNER JOHN JOHNSON
MAILING ADDRESS 10235 Black Hawk
Reno, Nevada 89506

ADDRESS AT WELL LOCATION 12000 Red Rock Road
Reno, Nevada 89506

2. LOCATION NW ¼ NW ¼ Sec. 24 T. 21N N/S R. 18E E. Washoe County
PERMIT NO. (Issued by Water Resources) 086-250-01 (Parcel No.) Red Rock Estates (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown clay, some volcanic gravels		1	9	8
Brown sandy clay		9	61	52
Light brown clay		61	120	59
Soft sandy brown clay		120	167	47
Soft zone (NO WATER)		167	178	11
Brown sandy clay		178	216	38
Soft zone	X	216	221	5
Brown clay		221	230	9
Soft zone	X	230	245	15
Brown clay		245	278	33
Soft zone	X	278	316	38
Brown clay		316	325	9

Date started 12-12-94, 19
Date completed 12-16-94, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
22		

8. WELL CONSTRUCTION
Depth Drilled 325 Feet Depth Cased 325 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	50	Feet
8 5/8	Inches	50	Feet	325	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	325

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 220 feet to 260 feet
From 280 feet to 320 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 325 feet

9. WATER LEVEL
Static water level 180 feet below land surface
Artesian flow G.P.M. 22 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date December 19, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627