WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 48300
Permit No.
Basin 162

NOTICE OF INTENT NO. 16052

DCNR/DWR Received JUL 10 1995 LAS VEGAS OFFICE

1. OWNER Marvin Munger
MAILING ADDRESS
ADDRESS AT WELL LOCATION 4901 E. McGraw

2. LOCATION SE ¼ NE ¼ Sec. 20 T 21-S N/S R 54 E Nye County
PERMIT NO. (Issued by Water Resources) 45-292-04 (Parcel No.) Green Saddle Ranch (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Surface		0	4	4
Sandy loam		4	10	6
Brown clay & gravel		10	56	46
Cemented gravel		56	62	6
Brown clay & gravel		62	74	12
Cemented gravel		74	82	8
Brown clay & gravel		82	92	10
Limestone/cement grav		92	108	16
Brn clay/grvl/caliche	X	108	171	63
Brown clay		171	208	37
Brown clay & caliche		208	221	13
Brown clay	X	221	276	55

Date started June 28, 19 95
Date completed June 28, 19 95

7. WELL TEST DATA

TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20	4	¼

8. WELL CONSTRUCTION
Depth Drilled 276 Feet Depth Cased 276 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 Inches		0 Feet	276 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.94	.188	0	276

Perforations:
Type perforation Torch Cut
Size perforation ¼" width 8" long
From 236 feet to 276 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured

Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 276 feet

9. WATER LEVEL
Static water level 56 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Jim Pike Well Drilling, LLC (Contractor)
Address P.O. Box 56 (Contractor)
Pahrump, NV 89041
Nevada contractor's license number issued by the State Contractor's Board 17563A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1812
Signed (By driller performing actual drilling on site or contractor)
Date June 30, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627