

Log No. **48505**
 Permit No. **087**
 Basin _____
 page 1 of 2 pages
 NOTICE OF INTENT NO. 22856

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Consultant:

1. OWNER: Broadbent & Associates, Inc. ADDRESS AT WELL LOCATION: _____
 MAILING ADDRESS 1000 Bible Way Suite 57 Allied Petroleum
Reno, Nevada 89502 2500 E. 4th St Reno, NV
 2. LOCATION: 1/4 087 1/4 Sec 7 T 19N N/S R. 20 E Washoe County _____
 PERMIT NO. M/O 702-A MW-5 008-228-01 E. Reno Area
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED: New Well Replace Recondition Deepen Abandon Other _____
 4. PROPOSED USE: Domestic Irrigation Test Municipal/Industrial Monitor Stock
 5. WELL TYPE: Cable Rotary RVC Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy silt: Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity.		0	4	4
Gravelly sand: Poorly graded sands, gravelly sands little or no fines.		4	16	12
Well-graded sand: Well graded sands, gravelly sands, little or no fines		16	18	2
Sandy gravel: Poorly-graded gravels, gravel-sand mixtures, little or no fines.		18	20	2
Boulder		20	22	2
Well-graded gravel: Well-graded gravels, gravel-sand mixtures, little or no fines.		22	50	28
Well-graded gravel: Well-graded gravels, gravel-sand mixtures little or no fines.		50	62	12
Clayey gravel: Clayey gravels, gravel sand				

Date started: 1/16/95, 19_____
 Date completed: 1/17/95, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

No. Test	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No Test			

8. WELL CONSTRUCTION

Depth Drilled: 84 Feet Depth Cased: 84 Feet

HOLE DIAMETER (BIT SIZE)

From _____ To _____
7 1/4 Inches 0 Feet 84 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		SCH 80	0	84
End Cap - Locking Cap				
8" steel flush mount.				

Perforations:

Type perforation: Factory sawed slot
 Size perforation: .020
 From 45 feet to 84 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout
 Depth of Seal: 3-37
 Placement Method: Pumped Poured
 Bentonite Seal: 37-41
 Gravel Packed: Yes No #3 Silica Sand:
 From 41 feet to 84 feet

9. WATER LEVEL

Static water level: 6.6 feet below land surface
 Artesian flow: N/A G.P.M. N/A P.S.I.
 Water temperature: N/A °F Quality: N/A

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name: Wayne Drilling Inc. Contractor
 Address: P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board: 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 908
 Signed: [Signature]
 By driller performing actual drilling on site or contractor
 Date: March 13, 1995

