WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. 48509
Permit No.
Basin 087

page 1 of 2 pages
NOTICE OF INTENT NO. 22856

Consultant:

~~1. OWNER~~ Broadbent & Associates, Inc.
MAILING ADDRESS 1000 Bible Way Suite 57
Reno, NV 89502

ADDRESS AT WELL LOCATION
Allied Petroleum
2500 E. 4th St. Reno, Nv

2. LOCATION ¼ 087 ¼ Sec. 7 T. 19N N/S R. 20 E. Washoe County

PERMIT NO. M/O 702-A SP-3 (Issued by Water Resources) | 008-228-01 (Parcel No.) | E. Reno Area (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravelly silt: Silty gravels, gravel-sand-silt mixtures.		0	5	5
Poorly-graded sand: Poorly grades sands, gravelly sands little or no fines.		5	15	10
Gravelly sand with cobbles: Well-graded sands, gravelly sands, little or no fines.		15	27	12
Boulder		27	29	2
Well-graded gravel: Well-graded gravels, gravel-sand mixtures, little or no fines.		27	32	5
Boulder:		32	34	2
Gravel and cobbles: Well- graded gravels, gravel-sand mixtures, little or no fines.		34	38	4
Silty Sand: Silty sands, sand-silt mixtures.		38	41	3
Sandy gravel: Poorly-graded gravels, gravel sand mixtures, little or no fines.		41	50	9
Sandy Gravel: (Continued on)				

Date started 1/17/95, 19
Date completed 1/18/95, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No Test			
Plugged by log 12459			

8. WELL CONSTRUCTION
Depth Drilled 80 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7¼ Inches		0 Feet	80 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		SCH 80	0	80
End cap-locking cap				
7" steel flush mount.				

Perforations:
Type perforation Factory sawed slot
Size perforation .020
From 75 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 2-65
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite Seal;65-71
Gravel Packed: ☒ Yes ☐ No #3 Silica Sand:
From 71 feet to 80 feet

9. WATER LEVEL
Static water level N/A feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date March 13, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 48909
Permit No.
Basin 087

page 2 of 2 pages
NOTICE OF INTENT NO. 22856

1. OWNER Broadbent & Associates Inc.
MAILING ADDRESS P.O. Box 12370
Reno, Nevada 89510

ADDRESS AT WELL LOCATION
Allied Petroleum
2500 E. 4th St Reno, Nv

2. LOCATION ¼ ¼ Sec. T. N/S R. E. County
PERMIT NO. M/O 702-A SP-3 (Issued by Water Resources) | 008-228-01 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Poorly-graded gravels, gravel-sand mixtures, little or no fines.		50	58	08
Sandy Clay: Clayey sands, sand-clay mixtures.		58	70	12
Gravel-sand silt: Silty gravels, gravel sand silt mixtures.		70	78	8
Sandy Silt: Silty sands, sand silt mixtures		78	80	2

Date started ..., 19..
Date completed ..., 19..

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ... Feet Depth Cased ... Feet

HOLE DIAMETER (BIT SIZE)

	From	To
... Inches	... Feet	... Feet
... Inches	... Feet	... Feet
... Inches	... Feet	... Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☐ No
From ... feet to ... feet

9. WATER LEVEL
Static water level ... feet below land surface
Artesian flow ... G.P.M. ... P.S.I.
Water temperature ... °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed (By driller performing actual drilling on site or contractor)
Date March 13, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627