

OFFICE USE ONLY  
Log No. 48587  
Permit No. 103  
Basin.

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 3122

Consultant: SWATER Klohn Leonoff Ltd. Client: Siskon Corporation  
MAILING ADDRESS: 10200 Shellbridge Way ADDRESS AT WELL LOCATION: 333 S. Carson Meadow Dr. Unit 44  
Richmond, B.C., Canada V6X2W7 Carson City, Nevada 89701  
2. LOCATION: SW 1/4 SW 1/4 Sec. 6 T. 16N N/S R. 21 E Storey County: Storey  
PERMIT NO. 0-195 Well KLDH-11 American Flat Valley  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
No Return		0	10	10
Clay, some silt, stone content increasing with depth, firm, moderately dense, dark brown		10	15	5
Andesite, dark grey to grey-black, some clay, moderately dense, firm, dark brown		15	49	34
Volcanics, reddish brown, reddish brown silt matrix, silt content increasing with depth		49	60	11
Volcanics, reddish brown and grey black, brown silt matrix		60	65	5
Andesite, greyish black, reddish brown silt matrix, matrix grading to clay with depth		65	80	15

8. WELL CONSTRUCTION  
Depth Drilled: 80 Feet Depth Cased: 80 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
6 1/8 Inches 0 Feet 80 Feet  
Inches Feet Feet  
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		Sch 40	0	80

Locking Monuments

Perforations:  
Type perforation: Factory Sawn Slot  
Size perforation: .020  
From 75 feet to 80 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal: 52'  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Bentonite Seal 52-61  Concrete Grout  
Gravel Packed:  Yes  No Lone Star #3  
From 61 feet to 80 feet

9. WATER LEVEL  
Static water level: 48 feet below land surface  
Artesian flow: \_\_\_\_\_ G.P.M. N/A P.S.I.  
Water temperature: N/A °F Quality: N/A

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name: Wayne Drilling, Inc. Contractor  
Address: P.O. Box 12370 Contractor  
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board: 22549  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 908  
Signed: [Signature]  
By driller performing actual drilling on site or contractor  
Date: July 11, 1994

Date started: September 27, 1989  
Date completed: September 27, 1989

7. WELL TEST DATA

TEST METHOD	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			