WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 48590
Permit No.
Basin 163

NOTICE OF INTENT NO. 3122

Consultant:
1. ~~OWNER~~ Klohn Leonoff Ltd.
MAILING ADDRESS 10200 Shellbridge Way
Richmond, B.C., Canada V6X2W7

Client:
ADDRESS AT WELL LOCATION Siskon Corporation
333 S. Carson Meadow Dr. Unit 44
Carson City, Nevada 89701

2. LOCATION SW ¼ SW ¼ Sec. 6 T 16N N/S R 21 E Storey County

PERMIT NO M/O-195 Well KLDH-4 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silt, clayey, low gravel content, light brown		0	8	8
Andesite, dark grey, light grey silty matrix		8	10	2
Volcanics, grey-brown, moderately stiff, medium plasticity, silty clay matrix from 10 to 15 ft., low plasticity silt matrix from 15.0 to 20.0 ft.		10	20	10
Andesite, dark grey, quartz inclusions, light grey to reddish brown, low plasticity slit matrix.		20	30	10

Date started September 28, 1989
Date completed September 28, 1989

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/8 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		sch 40	0	30
Locking Monuments				

Perforations:
Type perforation Factory Sawed Slot
Size perforation .020
From 10 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 3'
Placement Method: ☐ Pumped ☒ Poured
Bentonite Seal 3-8
Gravel Packed: ☒ Yes ☐ No
From 8 feet to 30 feet
Lone Star #3

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

9. WATER LEVEL
Static water level n/a feet below land surface
Artesian flow G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed [signature] (By driller performing actual drilling on site or contractor)
Date July 11, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627