X

SEE LOG # 38064

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

FOR USE ONLY
Log No. 48715
Permit No.
Basin 08

NOTICE OF INTENT 2157

1. OWNER Rodney Fair
MAILING ADDRESS 1646 Rev. Way Boulder City NV
ADDRESS AT WELL LOCATION 2570 Tacchino Ave. Reno NV

2. LOCATION SW ¼ SW ¼ Sec. 6 T. 19 N/S R. 20 E. Washoe County
PERMIT NO. R194-MO 493 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☒ Other Odex Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
The well was found to be in good condition, I removed the Christy box, perforated the bottom plug of the PVC Casing. Then, using a mix of water and portland type I-II cement mixed at a ratio of 6 gallons per sack, I tremied the grout into the well using about 30 gallons of grout.				

'94 JUL -8 P1:43
STATE ENGINEER

Date started 8-26, 1993
Date completed 8-26, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
		N/A

8. WELL CONSTRUCTION
Depth Drilled 52 Feet Depth Cased 52 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
5 Inches	0 Feet	52 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	Sch. 40	0	52

Perforations:
Type perforation Factory Slot
Size perforation .020 Inch
From feet to feet
From 42 feet to 52 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 37 feet Bentonite Plug 37-40'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 40 feet to 52 feet

9. WATER LEVEL
Static water level 47.9 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cold °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Andresen Exploration Drilling (Contractor)
Address 1635 Belford Rd. Reno NV. (Contractor)
RENO, NV. 89509
Nevada contractor's license number issued by the State Contractor's Board 34525
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1667
Signed [signature] By driller performing actual drilling on site or contractor
Date 6/13/94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627