WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45750
Permit No.
Basin 084

NOTICE OF INTENT NO. 26474

1. OWNER Consultant: Groundwater Resources Consultants, Inc.
MAILING ADDRESS 1735 East Fort Lowell Rd. #4
Tucson, Arizona 85719

ADDRESS AT WELL LOCATION
Client: Rocketdyne Former Field Lab
2640 Off Whiskey Spring Rd, Reno, Nev.

2. LOCATION SW ¼ NE ¼ Sec. 7 T 22N N/S R 22E E Washoe County
PERMIT NO. M/O-431B D-22A Issued by Water Resources | 77-320-04 69 Parcel No. | 7-2-3 Palomino Valley Unit 11 Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [X] Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Gravelly Clay, Medium brown, loose, gravel subangular to well rounded. @ 10' moist. @ 17' very moist. @ 25' wet.		0	25	25
Tuff, Light purplish grey unwelded rhyolite tuff.		25	30	5

Date started June 3, 19 94
Date completed June 4, 19 94

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
< 1		

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5		sch. 40	0	30

Perforations:
Type perforation Factory Sawed Slot
Size perforation 0.020 x 2"
From 19.5 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 13.5
Placement Method: [X] Pumped [ ] Poured
Bentonite Seal 15.5 - 13.5
Gravel Packed: [X] Yes [ ] No
From 30 feet to 15.5 feet
Lone Star #3

Seal Type:
[X] Neat Cement
[ ] Cement Grout
[ ] Concrete Grout

9. WATER LEVEL
Static water level 30.30 feet below land surface
Artesian flow G.P.M. < 1 P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. Contractor
Address P. O. Box 12370 Contractor
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] By driller performing actual drilling on site or contractor
Date July 6, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627