

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 26880

1. OWNER Ray Swanson ADDRESS AT WELL LOCATION Antelope Valley
 MAILING ADDRESS 10368 Fareway
Hanford, CA 93230
 2. LOCATION SW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 31 T. 25 N R 41 E Lander County
 PERMIT NO. 18716 Swanson Farms Subdivision Name
Issued by Water Resources Parcel No. _____

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Topsoil		0	3	3
Sand & Gravel		3	15	12
Sandy Clay		15	20	5
Sand & Gravel		20	25	5
Sandy Clay		25	33	8
Sand & Gravel		33	40	7
Sand w/gravel				
50% clay		40	50	10
Clay		50	70	20
Sand & Gravel		70	78	8
Clay		78	85	7
Sand & Gravel		85	100	15
Clay		100	113	13
Sand & Gravel		113	128	15
Clay		125	160	35
Clay w/small clay layers		160	165	5
Sand & Gravel		165	170	5
Sandy Clay		170	181	11
Sand & Gravel		181	195	14
Sandy Clay		195	200	5
Sand & Gravel		200	210	10
Sandy Clay		210	223	13
Sand & Gravel		223	233	10
Sandy Clay		233	238	5
Sand & Gravel		238	245	7
Sandy Clay		245	283	38
Sand & Gravel		283	310	27

8. WELL CONSTRUCTION
 Depth Drilled 310 Feet Depth Cased 300 Feet
 HOLE DIAMETER (BIT SIZE)
 From 24 Inches To 0 Feet 310 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	.250	0	110

 Perforations:
 Type perforation Mill slotted & louvered
 Size perforation 3 x 1/8
 From S louvered 110 feet to 130 feet
 From D.R.M.S. 130 feet to 170 feet
 From f.f. louvered 170 feet to 200 feet
 From D.R.M.S. 200 feet to 220 feet
 From S louvered 220 feet to 240 feet
 From D.R.M.S. 240 feet to 300 feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 50 Neat Cement
 Placement Method: Pumped Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 300 feet

Date started April 3, 1995
 Date completed April 5, 1995

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>2500</u>	<u>160'</u>	<u>10</u>

9. WATER LEVEL
 Static water level 8.0 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature NORM °F Quality good

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Humboldt Drilling & Pump Co Inc. Contractor
 Address P.O. Box 590 Contractor
Winnemucca, NV 89446
 Nevada contractor's license number issued by the State Contractor's Board 015234
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154
 Signed C. C. Oyle
 By driller performing actual drilling on site or contractor
 Date 4-28-95