WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 48956
Permit No.
Basin 089 104

NOTICE OF INTENT NO. 28020

1. OWNER Craig Lawson
MAILING ADDRESS 465 Duckhill Rd Carson City NV 89701
ADDRESS AT WELL LOCATION 465 Duckhill Rd Carson City NV
2. LOCATION SW ¼ NW ¼ Sec. 36 T. 16 N/S R. 20 E. Washoe County
PERMIT NO. (Issued by Water Resources) 55-270-04 (Parcel No.) 19? (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| DG Sands | | 0 | 15 | 15 |
| Coarse DG Sands | | 15 | 110 | 95 |
| Hard Granite (Hard) | | 110 | 125 | 15 |
| Rusty Coarse DG Sands (Hard) (Medium) | | 125 | 250 | 125 |
| (Very Hard) Blue Granite | | 250 | 275 | 25 |
| Broken DG Fractures DG Sands (Soft) | xx | 275 | 300 | 25 |
| T.D. 300' | | | | |
| GPM 15 gallons | | | | |

RECEIVED MAY 24 '95 9:50 AM
STATE ENGINEER'S OFFICE

Date started 5-20, 1995
Date completed 5-24, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 15 | 70 | 4 HRS |

8. WELL CONSTRUCTION
Depth Drilled 300' Feet Depth Cased 300' Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 10 3/4 Inches | | 0 Feet | 50 Feet |
| 9 7/8 Inches | | 50 Feet | 300 Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | 13.03 | .188 | 0 | 300 |

Perforations:
Type perforation Mill Slot
Size perforation 3 x 3/32
From 260 feet to 300 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55'
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 55 feet to 300 feet

9. WATER LEVEL
Static water level 160 feet below land surface
Artesian flow G.P.M. 15 P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H Pump Company (Contractor)
Address 5551 Hwy 50 E #3 Carson City NV 89701 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 31839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed Michael L Hack (By driller performing actual drilling on site or contractor)
Date 5-24-95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627