WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 48975
Permit No.
Basin 183

NOTICE OF INTENT NO. 21102

1. OWNER Kerry Lynn Holt/ George S. Holt ADDRESS AT WELL LOCATION Lakevalley Rd.
MAILING ADDRESS Box 249
Enterprise, Ut. 84725

2. LOCATION NE ¼ NW ¼ Sec. 33 T. 6 N/S R. 66 E. Lincoln County
PERMIT NO. 59112 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☑ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☑ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand, Clay		0	35	35
Clay		35	37	2
Sand, gravel		37	42	5
Clay		42	45	3
Sand, gravel		45	52	7
Sand, clay		52	95	43
Clay		95	110	15
Sand gravel		110	146	36
Clay		146	155	9
Sand Clay		155	168	13
Sand (fine)		168	186	18
Clay		186	198	12
Sand Clay		198	235	37
Clay		235	268	33
Sand Clay		268	277	9
Clay		277	289	12
Sand		289	296	7
Clay		296	314	18
Sand		314	321	7
Clay		321	326	5
Sand gravel		326	349	23
Sand, Clay		349	357	8
Sand, gravel		357	370	27

Date started 6-30-, 1995
Date completed 7-3-, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
N/A		

8. WELL CONSTRUCTION
Depth Drilled 370 Feet Depth Cased 370 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
28 Inches		0 Feet	370 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42 lb.	.250	18" +	370

Perforations:
Type perforation Mill
Size perforation 5/32 x 2.5
From 170 feet to 370 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 370 feet

9. WATER LEVEL
Static water level 110 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature Cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Gardner Drilling (Contractor)
Address Box 18 New Castle, Ut. 84756 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0031759
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1710
Signed Dale Gardner (By driller performing actual drilling on site or contractor)
Date July 10, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627