

LOG# 49145

Field Exploratory Boring Log VE-4

| OVM PPM | Blows/ 6" | Sample Number | Well Construction | Depth (ft) | Soil Group (USCS) | Materials Description |
|------------|--------------|------------------|--|---------------|------------------------|--|
| | | | Wellbox 0 - 1 Ft. | | Asphalt Silt (ML) | Brown (10YR 4/3); stiff, moist, 90% silt, 10% fine sand. |
| | | | Neat Cement | | Silty Sand (SM) | Dark Brown (10YR 3/3); dense, moist, 70-80% fine sand, 20-30% silt, subangular to rounded particles. |
| | | | Bentonite 4-7 Ft. | | Sand with Silt (SW-SM) | Dark Brown (10YR 3/3); dense, moist, 90% fine to coarse sand, 10% silt, subangular to rounded particles. |
| | | | 2-in. Sch. 40 PVC - Solid | 5 | Sand (SW) | Very Dark Gray (10YR 3/1); very dense, moist, 95% fine to coarse sand, 5% fine gravel, subangular to rounded particles. |
| | | | Coarse Aquarium Sand Sandpack | 10 | Gravel (GW) | Very Dark Gray (5 Y 3/1); very dense, moist to saturated, 75-85% fine to coarse gravel, 15-25% fine to coarse sand, subangular to rounded particles. |
| | | | 2-in. Sch. 40 PVC - 0.05-in. Mill Slot | 15 | | Groundwater encountered at approximately 17 feet. |
| | | VE-4 -15.5' | | 19 | | Total Depth of Boring = 19.0 ft. |

95 MAY -4 RH1-13
STATE ENGINEERS OFF

**BORING
VE-4**

UNOCAL CORPORATION - CERT
Former Unocal SS No. 6979
475 East Prater Way
Sparks, Nevada

Borehole Diameter: 6 inches
Logged by: C. Galantine
Driller: Westex
Date Started: 4-11-95
Date Completed: 4-11-95

enviros®
95109.09