WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49375
Permit No.
Basin 392B

NOTICE OF INTENT NO. 29553

1. OWNER Bob Kelly
MAILING ADDRESS 9980 Macauley Rd.
Reno, Nevada 89506

ADDRESS AT WELL LOCATION
1200 Estates
Reno, Nevada 89506

2. LOCATION NW ¼ NW ¼ Sec. 35 T. 21N N/S R. 19E E. Washoe County
PERMIT NO. (Issued by Water Resources) 080-730-18 (Parcel No.) Lemmon Valley (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	4	4
D.G.		4	10	6
D.G. with clays		10	16	6
Weathered Granite		16	23	7
Gray & Green Granite		23	123	100
Gray & Green Granite with weathered streaks		123	188	65
Fracture (no water)		188	190	2
Gray Granite		190	215	25
Fracture (no Water)		215	216	1
Gray Granite		216	224	8
Fracture (3 GPM)	X	224	225	1
Gray Granite		225	278	53
Fracture (3 GPM)	X	278	280	2
Gray Granite		280	299	19
Gray Granite with weathered streak.		299	300	1

Date started 6/19/95, 19
Date completed 6/22/95, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
6		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	300 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation Factory Sawed Slot
Size perforation 3/32 X 3 X 5 around
From 195 feet to 215 feet
From 275 feet to 295 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 138 feet below land surface
Artesian flow G.P.M. 6 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date June 26, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627