

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Page 1 of 2 pages

Consultant: 1. ~~OWNER~~ Hydro-Search, Inc.
 MAILING ADDRESS 5250 So. Virginia St. #280
 Reno, Nevada 89502
 Client: NOTICE OF INTENT NO. 20140
 ADDRESS AT WELL LOCATION Sparks Solvent/Fuel Site
 Glen Carran Circle
 Sparks, Nevada 89431
 2. LOCATION SW 1/4 NE 1/4 Sec 9 T 19N N/S R 20 E Washoe County
 PERMIT NO. M/O 396-A MW-205 On street N of Parcel 034-101-43
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Hand dug		0	5	5
Clayey Silt (CL), with rounded gravels.		5	9	4
Sand (SP/SM), medium brown (10YR 3/3), fairly well sorted, 12% fines, 5-10% rounded coarse gravels.		9	11	2
Cobbles and Gravel (GW), 20% coarse gravels, 30-50% fine gravel/coarse sand, 5% fines.		14	16	2
Same as above		19	21	2
Sand (SP), brown, 10YR 3/4, 30% rounded coarse gravels up to 3", 60% coarse sand, 5% fines.		24	26	2
Cobbles and Gravels (GW), brown (10YR 3/4), rounded, 40% poorly sorted coarse gravels, 40% coarse to medium sands, 5% fines.		29	31	2
Same as above, color change dark yellowish brown (10YR 6/8), increased fines, 12%		at	35	
Same as above		at	40	
Sand and Gravel (GM), yellowish brown (10YR 6/8), coarse, Poorly sorted.				

8. WELL CONSTRUCTION
 Depth Drilled 60 Feet Depth Cased 58.5 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
9 5/16 Inches 0 Feet 60 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5" PVC		Sch 80	0	58.5

 End Cap & Locking Cap
 Perforations:
 Type perforation Factory Sawn Slot
 Size perforation .060
 From 18 feet to 58 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 10' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal 10-13 Sand Filter 0/30
 Gravel Packed: Yes No
 From Lone Star 6/12 mesh fr. 15-58.8' feet 13-15' feet

Date started November 6, 1991
 Date completed November 8, 1991

7. WELL TEST DATA

TEST METHOD: Bailor Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test		

9. WATER LEVEL
 Static water level 25/5 feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed Harold Steadman
 By driller performing actual drilling on site or contractor
 Date July 12, 1994

