

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Page 1 of 2 pages

NOTICE OF INTENT NO. 20142

Consultant:

Client:

1. ~~XXXXXX~~ Hydro-Search, Inc.

ADDRESS AT WELL LOCATION Sparks Solvent/Fuel Site
Dunn Circle/ Watson Way
Sparks, Nevada 89431

MAILING ADDRESS 5250 So. Virginia St. #280
Reno, Nevada 89502

2. LOCATION SW 1/4 NW 1/4 Sec. 10 T. 19N. N/S R. 20 E. Washoe County

PERMIT NO. M/O 396A MW-207 Corner of Dunn & Watson E. of Parcel 034-311-07
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Fill, Sand (SM), fine grained, brown, with minor silt.		0	5	5
Fill, Sand (SM), fine grained, brown.		5	9	4
Fill, Sand (SW), fine well sorted, brown.		9	11	2
Sand (SW/SM), coarse to fine grained (60%) poorly sorted with poorly sorted gravels (40%) and cobbles, fine 5-12.		14	16	2
Sand and Gravel (GW/SW), 5% fines.		16	19	3
Gravelly Sand (SW/GM), (7.5yr 4/2), coarse sands, poorly sorted with fine to coarse gravel, occasional cobbles. Fines 5/12.		19	21	2
Sandy Silty Gravel (GW/GM), (7.5YR 4/2) poorly sorted with cobbles - moist. Well rounded cobbles, subrounded coarse gravel, fines 5%		24	26	2
Damp. Same as above.		29	31	2
Same as above. Saturated, slightly oxidized, less than 5% fines.		34	36	2
Same as above		39	41	2

8. WELL CONSTRUCTION
 Depth Drilled 64 Feet Depth Cased 62.5 Feet

HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 0 Feet 62.5 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5" PVC		Sch 80	0	62.5

End Cap & Locking Cap

Perforations:
 Type perforation Factory Sawn Slot
 Size perforation .060
 From 17 feet to 62 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout

Depth of Seal 9'

Placement Method: Pumped
 Poured

Bentonite Seal 9-12

Gravel Packed: Yes No Sand Filter 0/30 12-14'
 From One Star 6x12 mesh fr. 14-62.7 feet

9. WATER LEVEL
 Static water level 38.1 feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed Wayne Drilling, Inc. By driller performing actual drilling on site or contractor
 Date July 15, 1994

Date started November 8, 1991
 Date completed November 9, 1991

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test			

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340
 Client:

Page 2 of 2 pages

NOTICE OF INTENT NO. 20142

Consultant:

1. ~~OWNER~~ Hydro-Search, Inc. ADDRESS AT WELL LOCATION Sparks Solvent/Fuel Site
 MAILING ADDRESS 5250 So. Virginia St. #280 Dunn Circle
Reno, Nevada 89502 Sparks, Nevada 89431
 2. LOCATION SW 1/4 NW 1/4 Sec 10 T 19N N/S R 20 E Washoe County
 PERMIT NO. M/O 396A MW-207 Parcel No. _____ Subdivision Name _____
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Cont.	Material	Water Strata	From	To	Thick-ness
	Gravels (GW), poorly sorted with occasional rounded cobbles with coarse to medium sand				
	30% less than 5% fines.		at	45	
	Same as above to 64'		at	50	
	Silts and fines increase				
	5 to 12% (GW/GM)		at	55	
	Gravel (GW), poorly sorted gravels with coarse-medium sand 30%. Cobbles with				
	5-12% Fines.		at	64	

8. WELL CONSTRUCTION

Depth Drilled _____ Feet Depth Cased _____ Feet

HOLE DIAMETER (BIT SIZE)

From _____ To _____

_____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:

Type perforation _____
 Size perforation _____

From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout

Depth of Seal _____

Placement Method: Pumped Poured

Gravel Packed: Yes No
 From _____ feet to _____ feet

9. WATER LEVEL

Static water level _____ feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed [Signature] By driller performing actual drilling on site or contractor
 Date July 15, 1994

Date started _____, 19____
 Date completed _____, 19____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)