WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49923
Permit No.
Basin 087

NOTICE OF INTENT NO. 20717

Consultant:

1. ~~OWNER~~ Steffen Robertson & Kirsten
MAILING ADDRESS 1755 Plumb Lane, Suite 241
Reno, Nevada 89502

Client: Western Energetix
ADDRESS AT WELL LOCATION
1250 W. 4th St.
Reno, Nevada 89503

2. LOCATION DAAB ¼ ¼ Sec. 10 T 19N N/S R 19E E Washoe County
PERMIT NO. M/O 665-A-SVE WELL #2 (Issued by Water Resources) 006-223-07 (Parcel No.) Reno (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [X] Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.25	.25
Aggrogate Base		.25	1	.75
Silty Gravel With sand cobbles and boulders.		1	4	3
Brown Silty clay, low to medium plasticity, moist.		4	16.5	12.5
Silty Gravel with silt boulders, non-plastic		16.5	44.5	28

Date started 5-21-94, 19
Date completed 5-21-94, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No Test		

8. WELL CONSTRUCTION
Depth Drilled 44.5 Feet Depth Cased 44.5 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	44.5 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	15
Christy Box/ Locking Cap				
Sparge Point/ Line/ 2" KYA			(42.5"-44.5")	

Perforations:
Type perforation Factory Sawed Slot
Size perforation .020
From 15 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-10.9
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
Bentonite Seal: 10.9-13.3, 35-37.5
Gravel Packed: [X] Yes [ ] No Silica Sand
From 13.3-35 feet to 37.5-44.5 feet

9. WATER LEVEL
Static water level 18 feet below land surface
Artesian flow n/a G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date May 15, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627