

OFFICE USE ONLY
 Log No. 49926
 Permit No. _____
 Basin 087

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 21859
 ADDRESS AT WELL LOCATION 1250 W. 4th St., Reno, NV

Consultant:

1. OWNER Steffen Robertson and Kirsten
 MAILING ADDRESS 1755 East Plumb Lane #241
Reno, Nevada 89502

Client:
 ADDRESS AT WELL LOCATION 1250 W. 4th St., Reno, NV
Western Energetix
419 W. Plumb Lane, Reno, NV 89509

2. LOCATION DAAB 1/4 Sec. 10 T. 19N N/S R. 19 E Washoe County
 PERMIT NO. M/O 665 MW-2 006-223-07 Reno
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt (GP), roadbase.		0	3"	3"
Silty Gravel (GP), with cobbles, boulders, very dense, non-plastic, brown, slight moisture.		1	4	3
Silty Clay (CL), low plasticity, moist.		4	7	3
Silty Clay (CL), low to medium plasticity, moist, brown.		7	12	5
Sandy Clay (CL), with silt, very firm, low to non-plastic, moist, brown.		12	15	3
Silty Gravel (GP), with abundant cobbles, boulders.		15	27	12
Silty Gravel (GP), with boulders, wet, close to saturation.		27	30	3
Silty Gravel (GP), with boulders and clay stringers, wet.		30	44	14

8. WELL CONSTRUCTION
 Depth Drilled 44 Feet Depth Cased 37.5 Feet

HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 44 Feet
 Inches Feet Feet Feet
 Inches Feet Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC Blank		Sch 40	0	14.5
3/4" PVC Blank		Sch 80	0	41.5
2" KYA Sparge Point				

Perforations: Locking Cap/ Locking Well Protector
 Type perforation Factory Sawn Slot
 Size perforation .020
 From 14.5 feet to 38 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 9.5 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Bentonite Seal 9.5-12 & 38-41.5
 Gravel Packed: Yes No #3 Silica Sand 12-38'
 From #3 Aqua Sand Pack feet to 41.5-44 feet

9. WATER LEVEL
 Static water level n/a feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date July 18, 1994

Date started June 17, 1993
 Date completed June 17, 1993

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>no test</u>		