WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49930
Permit No.
Basin 087

NOTICE OF INTENT NO. 22873

Consultant:

1. ~~OWNER~~ Steffen Robertson & Kirsten
MAILING ADDRESS 1755 Plumb Lane, Suite 241
Reno, Nevada 89502

Client: Western Energetix
ADDRESS AT WELL LOCATION 350 Arlington Ave.
Reno, Nevada 89501

2. LOCATION DC ¼ ¼ Sec. 11 T. 19N N/S R. 19E E. Washoe County

PERMIT NO. M/O-688-B S-2 (Issued by Water Resources) | 011-156-16 (Parcel No.) | City of Reno (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.25	.25
Silty Sand		.25	5	4.75
Silty Sand		5	10	5
Sandy Gravel with cobbles and boulders.		10	50	40
Silty Gravel with cobbles and boulders.		50	70	50

Date started 10-21-94, 19
Date completed 10-21-94, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No Test			

8. WELL CONSTRUCTION
Depth Drilled 70 Feet Depth Cased 70 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 1/8 Inches		0 Feet	70 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
PVC 3/4"		SCH 80 PVC	0	68
Locking Well Protector/Locking Cap				
PVC Sparge Point with .02" Slots				

Perforations:
Type perforation Factory Sawed Slot
Size perforation .020
From 68 feet to 70 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-4.5
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite Seal: 4.5-7.5, 63-67
Gravel Packed: ☒ Yes ☐ No #3 Silica Sand
From 7.5-63 feet to 67-70 feet

9. WATER LEVEL
Static water level 50 feet below land surface
Artesian flow n/a G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (by driller performing actual drilling on site or contractor)
Date May 15, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627