WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49932
Permit No.
Basin 087

Consultant: Client

NOTICE OF INTENT NO. 21870

1. OWNER Steffen Robertson and Kirsten
MAILING ADDRESS 1755 East Plumb Lane #24
Reno, Nevada 89502

ADDRESS AT WELL LOCATION 1600 B St., Sparks, Nv.
Western Energetix 1600 Victorian Ave.
419 W. Plumb Lane, Reno, Nv 89509

2. LOCATION SE ¼ SW ¼ Sec. 5 T 19N N/S R 20 E Washoe County
PERMIT NO. M/O 655 MW-1 (Issued by Water Resources) 032-122-18 (Parcel No.) Sparks (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt Concrete		0	2.5'	2.5'
Gravelly Sand (GP), (up to 5" in cobbles) non-plastic, brown, slight moisture, medium dense.		2.5'	12'	11'9.5'
Silty Gravels (GM), some to considerable sand, low plasticity to non-plastic, brown, moist to saturated.		12	19.5	7.5
Silty Gravels with Sand (GM), grey to brown, moisture content increasing, (vadose zone of high water table)		19.5	40	20.5

Date started April 15, 1993
Date completed April 15, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test			

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 1/4 Inches		0 Feet	40 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC	Blank	Sch 40	0	9
End Cap/ Locking Cap & Locking Christie Box				

Perforations:
Type perforation Factory Sawed Slot
Size perforation .020
From 9 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 6'
Placement Method: ☐ Pumped ☒ Poured
Bentonite Seal 6-8
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No #3 Silica Sand 8-39.5
From 8 feet to 39.5 feet

9. WATER LEVEL
Static water level n/a feet below land surface
Artesian flow n/a G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed (By driller performing actual drilling on site or contractor)
Date July 18, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627