WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49936
Permit No.
Basin 087

Consultant: Client:

NOTICE OF INTENT NO. 23366

1. OWNER Steffen Robertson and Kirsten
MAILING ADDRESS 1755 East Plumb Lane #241
Reno, Nevada 89502

ADDRESS AT WELL LOCATION 1600 B St. Sparks, Nv
Western Energetix 1600 Victorian Ave.
419 W. Plumb Lane, Reno, Nv 89509

2. LOCATION C ¼ ¼ Sec 5 T 19N N/S R 20 E Washoe County
PERMIT NO. M/O-655-B MW-5 (Issued by Water Resources) 032-122-18 (Parcel No.) Sparks (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Ashaltic Concrete		0	3"	3"
Grey Black Aggregate Base (GP), with trace of cobbles.		3"	1.3	1
Brown Clayey Sands (SC), medium plasticity, medium dense, slightly moist.		1.3	2.5	1.2
Brown Silty Gravels (GM), with trace cobbles, non-plastic, loose, slightly moist.		2.5	19.3	16.8
Greyish Brown Silty Gravels (GM), with trace cobbles and boulders; low plasticity, loose, saturated.		19.3	22	2.7
Brown Silty Gravels (GM), no plasticity, loose, saturated.		22	38.5	16.5

Date started August 11, 1993
Date completed August 11, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test		

8. WELL CONSTRUCTION
Depth Drilled 38.5 Feet Depth Cased 33.8 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	38.5 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC	Blank	Sch 40	0	13.8
3/4 PVC		Sch 80	0	37.9
2" PVC	Sparge	.020 Slot	36.5	38.5

Perforations: Locking Cap & Christy Box
Type perforation Factory Sawed Slot
Size perforation .020
From 13.8 feet to 33.8 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 9.4
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite Seal 9.4-11.8 & 33.8-35.9
Gravel Packed: ☒ Yes ☐ No #8 Silica 11.8-33.8
From Pea Gravel ~~feet to~~ 35.5-38.5 feet

9. WATER LEVEL
Static water level n/a feet below land surface
Artesian flow n/a G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date July 19, 1994

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627