

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 21854

Consultant: _____

1. OWNER Steffen Robertson and Kirsten Client: _____
 MAILING ADDRESS 1755 East Plumb Lane #241 ADDRESS AT WELL LOCATION 2169 Prater Way, Sparks, Nevada 89502
Reno, Nevada 89502 Western Energetix
419 W. Plumb Lane, Reno, Nv. 89509

2. LOCATION DD 1/4 Sec. 6 T. 19N N/S R. 20 E. Washoe County Sparks
 PERMIT NO. M/O 687 MW-1 032-023-01 Subdivision Name _____
Issued by Water Resources Parcel No.

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphaltic Concrete		0	3"	3"
Aggregate Base		3"	1'	9"
Dark Brown Gravel (GP), with considerable silty sand and trace cobble; none-plastic, slightly moist.		7"	1'	5"
Dark Brown Gravels (GP), with loose sand; non-plastic, low density, moist.		1	11	10
Dark Brown Angular Silty Gravels (GM); non-plastic, medium dense, moist.		11	18.5	7.5
Brown Angular Sandy Gravels (GP), non-plastic, loose, moist.		18.5	26.5	8
Light Brown Clayey Gravels (GC), angular, medium dense, low plasticity, moist.		26.5	30.75	4.25
Dark Brown Clayey Sands (SC), low plasticity, medium dense, moist.		30.75	32	1.25
Dark Brown Silty Gravel (GM), loose, non-plastic, very moist to saturated.		32	50	18

Note: at 36' color change to dark to light brown.

8. WELL CONSTRUCTION
 Depth Drilled 50 Feet Depth Cased 44 Feet

HOLE DIAMETER (BIT SIZE)
 From To
9 5/16 Inches 0 Feet 50 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC	Blank	Sch 40	0	19.5
3/4" PVC		Sch 80	0	48
2" KYA	Sparge		48	50

Perforations: Locking Cap/Locking Well Protector
 Type perforation Factory Sawn Slot
 Size perforation .020
 From 19.5 feet to 44 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout

Depth of Seal 15

Placement Method: Pumped
 Poured

Bentonite Seal 15-17 & 44-48
 Gravel Packed: Yes No #3 Silica 17-44
 From #3 Silica XXXX 48-50 feet

9. WATER LEVEL
 Static water level n/a feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date July 19, 1994

Date started July 27, 1993
 Date completed July 27, 1993

7. WELL TEST DATA

TEST METHOD	<input type="checkbox"/> Bailer	<input type="checkbox"/> Pump	<input type="checkbox"/> Air Lift
<u>no test</u>			

Draw Down (Feet Below Static) _____ Time (Hours) _____