

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 27285

Consultant: Harding Lawson Associates Client: \_\_\_\_\_  
 1. OWNER: \_\_\_\_\_ ADDRESS AT WELL LOCATION: \_\_\_\_\_  
 MAILING ADDRESS 961 Matley Lane, Suite 110 Nevada Department of Transportation  
Reno, Nevada 89502 Pyramid Way Interchange Sparks, Nevada  
 2. LOCATION NW 1/4 NW 1/4 Sec 9 T. 19 N/S R 20 E. Washoe County  
 PERMIT NO. M/O 816 MW-6 032-220-47 Sparks  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED 4. PROPOSED USE 5. WELL TYPE  
 New Well  Replace  Recondition  Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Deepen  Abandon  Other \_\_\_\_\_  Municipal/Industrial  Monitor  Stock  Air  Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Poorly graded sand with silt and gravel; dense, moist, fill.		0	1	1
Brown poorly graded sand with gravel and cobbles; dense, moist, cobbles, pieces of metal, brick, fill.		1	3	2
Black Poorly Graded Sand; medium dense, dry, pieces of metal and brick, ash, fill		3	4	1
Brown Sandy Lean clay with gravel; firm, moist		4	8	4
Brown Poorly Graded Sand with Gravel; moist, trace clay. (Decreasing sand content, increasing gravel and cobble content).		8	34	26

8. WELL CONSTRUCTION  
 Depth Drilled 34 Feet Depth Cased 34 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 7 1/2 Inches To 0 Feet 34 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		SCH 40	0	34

Locking Cap / End Cap  
Steel Well Cover

Perforations:  
 Type perforation Factory Sawed Slot  
 Size perforation .020  
 From 14 feet to 34 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 0-9  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite Seal: 9-11  
 Gravel Packed:  Yes  No Lone Star #3  
 From 11 feet to 34 feet

9. WATER LEVEL  
 Static water level: 22.69 8/4/94 feet below land surface  
 Artesian flow N/A G.P.M./A \_\_\_\_\_ P.S.I.  
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc Contractor  
 Address P.O. Box 12370 Contractor  
Reno, Nevada 89510

Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources the on-site driller: 908  
 Signed Wayne Drilling Inc  
 by driller performing actual drilling on site or contractor  
 Date April 4, 1995

Date started 7/20/94, 19\_\_\_\_  
 Date completed 7/20/94, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No Test			