

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Client: Western Energetix NOTICE OF INTENT NO. 21858

Consultant: Steffen Robinson & Kirsten
 MAILING ADDRESS 1755 Plumb Lane #241
Reno, Nevada 89502
 ADDRESS AT WELL LOCATION Winners Corner
2191 Pyramid Way
Sparks, Nevada 89431
 2. LOCATION DDDA 1/4 1/4 Sec 32 T 20N N/S R 20 E Washoe County
 PERMIT NO. M/O 656 MW-4 027-342-06 Sparks
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt		0	3"	3"
Silty Sand (SM), with gravel, loose, non-plastic, black-brown, moist.		3"	4'	3'9"
Clayey Sand (SC), stratified with sandy, gravelly, layers, stiff, low to medium plasticity, brown.		4	11	7
Silty Gravel (GM), with abundant sand, dense, non-plastic, green-brown, moist.		11	20	9
Wet at 20.				
Cobbles & Gravel (GP), saturated.		20	24	4
Sand (SP), with minor gravel.		24	28.5	4.5
Clay with Sandy Lenses (CL), brown, saturated, high plasticity.		28.5	31	1.5
Clay (CL), high plasticity, saturated, brown.		31	34.5	3.5

8. WELL CONSTRUCTION
 Depth Drilled 34.5 Feet Depth Cased 34.5 Feet
 HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 0 Feet 34.5 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		Sch 40	0	34.5
3/4" PVC		SCH 80 Sparge Line	0	32
Sparge Point			32	34.5

Perforations: Locking cap/Locking well protector
 Type perforation Factory Sawn Slot
 Size perforation .020
 From 12 feet to 26 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 0-8 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal 8-10 & 26-27
 Gravel Packed: Yes No Silica Sand #3
 From 10 to 26 and _____ feet to 27 to 34.5 feet

9. WATER LEVEL
 Static water level 21.3 feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number 22549
 issued by the State Contractor's Board.
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date January 4, 1994

Date started June 9 1993
 Date completed June 9 1993

7. WELL TEST DATA

TEST METHOD	TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift		
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			