

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 21858

Consultant:

Client: Western Energetix

1. ~~OWNER~~ Steffen Robinson & Kirsten
 MAILING ADDRESS 1755 Plumb Lane #241
 Reno, Nevada 89502

ADDRESS AT WELL LOCATION Winners Corner
 2191 Pyramid Way
 Sparks, Nevada 89431

2. LOCATION DDDA 1/4 Sec 32 T 20N N/S R 20 E Washoe County
 PERMIT NO. M/O 656 MW-5 027-342-06 Sparks
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	3"	3"
Fill (GP), gravel.		3"	2'	1'9"
Silty Sand (SM), loose, low plasticity, brown to black, moist.		2	3	1
Silty Sand (SM), loose, non-plastic, green grey.		3	4.5	1.5
Silty Clay (CL), medium plasticity, brown, moist.		4.5	8	3.5
Sandy Clay (CL), stiff, medium to low plasticity, brown, moist.		8	12	4
Sandy Gravel (GP), with occasional cobbles, silt, non-plastic, moist, brown with green-red cobbles.		12	19	7
Sandy Gravel (GP), with cobbles, non-plastic, moist.		19	23	4
Sand (SP), with gravel Clay (CL), brown, saturated, high plasticity.		23	30	7
		30	32	2

8. WELL CONSTRUCTION
 Depth Drilled 32 Feet Depth Cased 32 Feet

HOLE DIAMETER (BIT SIZE)

From	To
9 5/16 Inches	0 Feet 32 Feet
Inches	Feet Feet
Inches	Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		Sch 40	0	25
3/4" PVC		SCH 80 Sparge line	0	31
Sparge Head			31	32

Perforations: Locking cap and Locking Well Protector
 Type perforation Factory Sawn Slot
 Size perforation .020
 From 10 feet to 30 feet
 From feet to feet
 From feet to feet
 From feet to feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 0-7' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal 7-9, 25-28
 Gravel Packed: Yes No Silica Sand #3
 From 9 to 25 and feet to 28 to 32 feet

9. WATER LEVEL
 Static water level 21.3 feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
 Reno, Nevada 89510
 Nevada contractor's license number 22549 issued by the State Contractor's Board
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed *Wayne Drilling, Inc.*
 By driller performing actual drilling on site or contractor
 Date January 4, 1994

Date started June 9, 1993
 Date completed June 9, 1993

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			