

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

Page 1 of 2 pages

Consultant:

Client: Western Energetics NOTICE OF INTENT NO. 21858

1. ~~XXXXX~~ Steffen Robinson & Kirsten
 MAILING ADDRESS 1755 Plumb Lane #241
 Reno, Nevada 89502

ADDRESS AT WELL LOCATION Winners Corner
 2191 Pyramid Way
 Sparks, Nevada 89431

2. LOCATION DDDA 1/4 1/4 Sec 32 T 20N N/S R 20 E Washoe County
 PERMIT NO. M/O 656 MW-6 027-342-06 Sparks Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex 190

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|---|--------------|------|----|------------|
| Asphalt & Base | | 0 | .5 | .5 |
| Silty Sand (SM) 80% medium to fine sand, 40% silt, black. | | | | |
| Silty Sand (SM), 80% medium sand, 40% silt, reddish brown, loose, moist, construction fill. | | .5 | 4 | 3.5 |
| Sandy Silty Clay (CL/ML). 40% clay, 35% silt, 25% sand, medium brown soft. moist to wet. | | 4 | 8 | 4 |
| Sandy Gravel (GW), 80% gravel, 35% sand 6% minor silt, gravel, clasts up to 5/8", round to subround, granitic, dense, damp. | | 8 | 12 | 4 |
| Sandy Gravel (GW), as above, 75% gravel, 25% sand, minor silt < 5%, gravel clasts to 2" dark gray, damp. | | | | |
| Interbeds of sand (medium to coarse) gravel (up to 3") 3" cobbles @ 20.0 ft. | | | | |
| water level-20.0 ft. | | 12 | 22 | 10 |
| Grades to gravelly silty sand, 80% sand, 25% clayey silt, 15% gravel up to | | | | |

8. WELL CONSTRUCTION
 Depth Drilled 28.5 Feet Depth Cased 28.5 Feet

HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 28.5 Feet
 Inches Feet Feet
 Inches Feet Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 4" PVC | | sch 40 | 0 | 28.5 |

End Cap & Locking Cap / Locking Well Protector

Perforations:
 Type perforation Factory Sawn Slot
 Size perforation .020
 From 8 feet to 28.5 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 0-5 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal 5-7
 Gravel Packed: Yes No Silica Sand #3
 From 7 feet to 28.5 feet

9. WATER LEVEL
 Static water level 20.0 feet below land surface
 Artesian flow n/a G.P.M. n/a P.S.I.
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date July 12, 1994

Date started June 10, 1993
 Date completed June 10, 1993

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---------|-------------------------------|--------------|
| No test | | |
| | | |
| | | |
| | | |

