WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 50181
Permit No.
Basin 089

NOTICE OF INTENT NO. 31866

1. OWNER Dennis Bush
MAILING ADDRESS 966 Jasper Way
Fernely, NV 89408

ADDRESS AT WELL LOCATION
3105 Holly Way
Carson City, NV 89704

2. LOCATION SW ¼ NW ¼ Sec. 5 T 16 N/S R 20 E Washoe County
PERMIT NO. 050-450-04 (Issued by Water Resources) Parcel No. New Washoe City (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [X] Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TAn, White, Yellow Brown D.G. Sand		0	17	
Green White Course Gravel		17	21	
TAn, White, Yellow Fine D.G. Sand		21	35	
Blk, White, Brown Semi Decomposed Granite		35	115	
Black & White, Gray Granite (hard)		115	140	
Black & White, Gray Granite (med hard) w/multiple fractures)	X	140	300	
T.D. 300'				

Date started November 18, 1995
Date completed November 28, 1995

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		2 hours

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10-5/8 Inches	0 Feet	53 Feet
8-1/2 Inches	53 Feet	140 Feet
6-1/8 Inches	140 Feet	300 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+1	140
5"		188	120	300

Perforations:
Type perforation Factory Sawed
Size perforation 3/32 x 3
From 140 feet to 120 feet
From 300 feet to 280 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 53
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 140 feet to 53 feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name A.S.A.P. Pump & Well Service, Inc. (Contractor)
Address 1800 1/2 Frazer Ave. (Contractor)
Sparks, Nevada 89431

Nevada contractor's license number issued by the State Contractor's Board 35387-A

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1509

Signed Larry Welch (By driller performing actual drilling on site or contractor)

Date November 29, 1995

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627