WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 50456
Permit No.
Basin 0 [illegible]

NOTICE OF INTENT NO. 32908

1. OWNER Ignacio & Lynn Herrera
MAILING ADDRESS 8275 Stinson Rd.
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
8275 Stinson Rd.
Winnemucca, NV 89445

2. LOCATION ¼ NW ¼ Sec. 24 T. 35 N/S R. 37 E. Humboldt County
PERMIT NO. (Issued by Water Resources) 14-111 (Parcel No.) Lot #15 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay		0	20	20
Sand & Gravel		20	28	8
Sandy Clay		28	40	12
Sand & Gravel		40	46	6
Sandy Clay		48	65	17
Sand & Gravel		65	78	13
Sand & Clay		78	85	7
Sand & Gravel		85	128	43

Date started June 26, 1995
Date completed June 26, 1995

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		

8. WELL CONSTRUCTION
Depth Drilled 128 Feet Depth Cased 119 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	128 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	99

Perforations:
Type perforation Mill Slot
Size perforation 1/8 x 2" Double Row
From 99 feet to 119 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 128 feet

9. WATER LEVEL
Static water level 47 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co Inc. (Contractor)
Address P O Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 7/12/95

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627