WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 50001
Permit No.
Basin 012

NOTICE OF INTENT NO. 30776

1. OWNER Pegasus Gold Corp.
MAILING ADDRESS P. O. Box 330
Imlay, NV 89418

ADDRESS AT WELL LOCATION Florida Canyon Mine, South of Exit 138, I-80

2. LOCATION SE ¼ NW ¼ Sec. 3 T. 31N N/S R. 33 E. Pershing County
PERMIT NO. M/O-973 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravel		0	20	20
Gravel/silt		20	80	60
Med. gravel		80	135	55
Gravel/Silt		135	150	15
Course gravel		150	175	25
Gravel/sand		175	200	25
Gravel	X	200	228	28

10' cement seal on top of hole to hold monument in place.

Date started Sept. 8, 19 95
Date completed Sept. 9, 19 95

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
3		3

8. WELL CONSTRUCTION
Depth Drilled 228 Feet Depth Cased 228 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8½ Inches		0 Feet	228 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4½		Sch. 80	+2	228

Perforations:
Type perforation Slot
Size perforation .020
From 188 feet to 228 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 178
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [ ] Concrete Grout [X] Bentonite Grout
Gravel Packed: [X] Yes [ ] No
From 178 feet to 228 feet

9. WATER LEVEL
Static water level 185 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature warm °F Quality poot

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hackworth Drilling, Inc. (Contractor)
Address P. O. Box 850 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 020582
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1995
Signed (By driller performing actual drilling on site or contractor)
Date September 12, 1995

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627