WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 50667
Permit No.
Basin 9

NOTICE OF INTENT NO. 32922

1. OWNER John McGurty
MAILING ADDRESS 5205 Paradise Rancheros Drive
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION 5205 Paradise Rancheros Drive
Winnemucca, NV 89445

2. LOCATION SE ¼ SE ¼ Sec. 13 T 39 N/S R 38 E Humboldt County

PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay		0	18	18
Sand & Gravel		18	35	17
Clay		35	40	5
Clay, Sand & Gravel		40	45	5
Clay		45	50	5
Sand & Gravel		50	54	4
Clay		54	60	6
Clay, Sand & Gravel		60	70	10
Sand & Clay Streak		70	88	18
Clay w/small streaks of sand & gravel		88	140	52

Date started 6-19-95, 19
Date completed 6-19-95, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		

8. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 129 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	140 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		3/16	+1	89

Perforations:
Type perforation Mill Slot
Size perforation 1/8 x 2"
From 89 feet to 129 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 140 feet

9. WATER LEVEL
Static water level 47 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co Inc. (Contractor)
Address P O Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154
Signed (By driller performing actual drilling on site or contractor)
Date 7/12/95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627