WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51022
Permit No.
Basin 212

NOTICE OF INTENT NO. 16243

1. OWNER Micheal Denton
MAILING ADDRESS Same

ADDRESS AT WELL LOCATION 8080 Alexito
Las Vegas, Nev.

2. LOCATION SE ¼ SW ¼ Sec 7 T 19 N/S R 59 E Clark County
PERMIT 470-340-038 (Issued by Water Resources) | 470-340-038 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravel		0	280	
Solid Rock		280	335	
Yellowish Rock		335	340	
Solid Limestone		340	390	
Cream Colored Rock	x	390	395	
Rock Cream Colored		395	438	
Black Rock		438	450	
Yellowish Rock		450	455	
Hard Limestone		455	470	
Yellowish Rock	xx	470	473	
Hard Limestone		473	478	
Yellowish Rock		478	485	
Black Rock		485	490	
Hard Limestone	x	490	495	
Yellowish Rock		495	500	

DCNR-DIV. OF WATER RESOURCES
Received JAN 17 1996
LAS VEGAS OFFICE

Date started 12/12/95, 19
Date completed 12/21/95, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 500 Feet Depth Cased 500 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 1/4"	Inches	0 Feet	55 Feet
11	Inches	55 Feet	500 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.94	.188	1	500

Perforations:
Type perforation Factory
Size perforation 3/16 x 8 row
From 460 feet to 480 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☒ Poured
Gravel Packed: ☐ Yes ☒ No
From feet to feet

Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

9. WATER LEVEL
Static water level 390 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name V.H. Dimick (Contractor)
Address 5360 Bonita Vista (Contractor)
Las Vegas, Nev. 89129

Nevada contractor's license number issued by the State Contractor's Board 10062
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 552

Signed (By driller performing actual drilling on site or contractor)
Date 12-21-95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627