WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51162
Permit No.
Basin 089 (1047)

NOTICE OF INTENT NO. 32603

1. OWNER Gregg & Carrie McAninch
MAILING ADDRESS 4591 Combs Canyon Rd
Carson City NV 89703
ADDRESS AT WELL LOCATION Not Assigned

2. LOCATION SW ¼ NW ¼ Sec. 36 T. 16 N/S R. 20 E. 19E ? Washoe County
PERMIT NO. (Issued by Water Resources) 055-320-54 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	2	2
Course Dk Sands		2	200	198
Course Rusty Dk Granite		200	395	195
Course Rusty Granite Contact Zone (Water)		395	410	15
Solid Hard Granite		410	600	190
Broken Blue Granite Fracture	xx	600	603	3
HARd Granite		603	610	7
Broken Fracture	xx	610	614	4
Hard Blue Granite		614	627	13
Broken Granite Fracture	xx	627	630	3
HARd Blue Granite		630	645	15

Date started 10-23, 1995
Date completed 11-3, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10-12	40	3 HRS

8. WELL CONSTRUCTION
Depth Drilled 645 Feet Depth Cased 645 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11¼ Inches		0 Feet	50 Feet
9 7/8 Inches		50 Feet	645 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	0	645

Perforations:
Type perforation Mill Slot
Size perforation 3 x 3/32
From [redacted] feet to [redacted] feet
From 605 feet to 625 feet
From 625 feet to 645 feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 55 feet to 645 feet

9. WATER LEVEL
Static water level 530 feet below land surface
Artesian flow G.P.M. 10-12 P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H Pump Company (Contractor)
Address 5551 Hwy 50 E #3 (Contractor)
Carson City NV 89701
Nevada contractor's license number issued by the State Contractor's Board 31839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed Michael L Hack (By driller performing actual drilling on site or contractor)
Date 11-5-95

RECEIVED 1995 NOV 20 AM 2:04 STATE ENGINEER'S OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627