



WELL NUMBER SL-3S

SHEET 1 OF 1

PROJECT Schering Laboratories

LOCATION Moya Blvd., Stead, NV

PROJECT NUMBER 108271219

LOGGED BY J. Stimson

LOCATION
COORDINATES:
ELEVATION

DATUM

| DEPTH FEET | LAB SAMPLE | SAMPLE DEPTH | TPH-DIESEL (mg/Kg) | PID READING (ppm) | H2O LEVEL | GRAPHIC LOG | DESCRIPTION | WELL COMPLETION DETAIL |
|------------|------------|--------------|--------------------|-------------------|-----------|-------------|--|---|
| 0-2' | | | | | | | 0-2': Clayey sandy silt (ML), dry, brown, silt with coarse to fine, polyimictic sand, and clay with occasional gravel up to 5 mm in diameter. Crumbles with moderate ease. | Cement seal between surface and 3'. |
| 2-8' | SL3S-5' | 5.0 | | 0.00 | | | 2-8': Clayey sandy silt (ML), moist, brown, silt with coarse to fine, polyimictic sand and clay. Crumbles with ease. | Bentonite plug between 3 and 4'. |
| | | 7.0 | | | | | @ 7': first wet formation outtings noted. | 2" SCH 40 solid PVC casing between 0 and 5'. |
| 8-11' | SL3S-10' | 10.0 | | 1.00 | | | 8-11': Silty sand (SM), wet, greenish-brown, medium to fine, polyimictic, subangular, well-sorted sand with silt. Crumbles with ease. | #3 sand filter pack between 4 and 30'. |
| | | 12.0 | | | | | 11-16': Silty clay (CL), wet, brown clay with silt, with minor, polyimictic sand up to 1 mm in diameter. Crumbles with ease. | |
| 15-16' | SL3S-15' | 15.0 | | 1.00 | | | | 2" SCH 40 0.02" slotted PVC screen between 5 and 30'. |
| 16-21.5' | | 17.0 | | | | | 16-21.5': Silty sand (SM), wet, greenish-brown, medium to fine, polyimictic, subangular, well-sorted sand with silt. Crumbles with ease. | |
| 20-21.5' | SL3S-20' | 20.0 | | 1.00 | | | | |
| | | 22.0 | | | | | | |
| 21.5-29' | SL3S-25' | 25.0 | | 0.75 | | | 21.5-29': Clayey sandy silt (ML), wet, brown, silt with clay and medium to fine, polyimictic, subangular sand, up to 1 mm in diameter. Crumbles with difficulty. | |
| | | 27.0 | | | | | @ 25-29': greater sand content, up to 2 mm in diameter. | |
| 29-30' | SL3S-30' | 30.0 | | 0.75 | | | 29-30': Silty sand (SM), wet, greenish-brown, coarse to fine, polyimictic, angular to subangular, moderately-sorted sand, up to 2 mm in diameter, with silt. Crumbles with ease. | |
| | | 32.0 | | | | | | |

DRILLING CONTRACTOR WESTEX
 HOLE DIAMETER 8.5"
 DRILLING METHOD Hollow stem auger
 DRILLING EQUIPMENT Mobile B-61 HDX
 DRILLING STARTED 10/31/95 ENDED 11/1/95

REMARKS Water level measured on 11/3/95.